

| المواد           |  |   |       |                |
|------------------|--|---|-------|----------------|
| اضافات الباطون   |  |   |       |                |
| Product          | سبب الإستخدام  | Description   | Size  | Coverage       |
| SikaControl-3760 | مضاف للباطون يعمل على جعل الباطون عازل للمياه  | crystalline powder admixture which becomes an integral part of concrete and is used to produce waterproof concrete. It is designed for use in above-grade and below-grade applications            | 25KG  | 25KG/9M3       |
| SikaControl 707  | مضاف للباطون يعمل على جعل الباطون عازل للمياه  | A liquid admixture for concrete to give high water resistance, based upon a blend of surface active agents and refined lignosulphonate. Suitable for use in hot and tropical climatic conditions. | 20L   | 1L/M3          |
| SikaFiber 012    | يضاف للباطون لتقليل التشققات الشعرية   | a high-performance monofilament polypropylene fibre developed as a crack controlling additive for concrete and mortar   | 0.6KG | 0.6KG/M3       |
| SikaLatex-141    | مضاف للخلطات الاسمنتية مثل القسارة والكحلة لإعطاء القوة وتقليل امتصاص المياه وتقليل التشققات | (SBR) styrene-butadiene co-polymer latex admixture to increase resistance to water penetration, improve abrasion resistance and durability  | 20L   | 1L/10KG CEMENT |

| العزل                |   |  |      |                          |
|----------------------|---|--|------|--------------------------|
| عزل مائي الأسطح      |   |  |      |                          |
| Product              | سبب/مكان الإستخدام  | Description  | Size | Coverage                 |
| SikaLastic 640P      | يستخدم كمادة أساس لعزل الأسطح الخارجية                      | Single component polyurethane primer for absorbent substrates prior to application of MasterSeal M 640 @ one coat  | 17KG | 80-100M2                 |
| SikaLastic 640M      | يستخدم لدهان الاسطح الخارجية للعزل المائي كفاءة عالية جدا   | Cost effective, one-component, liquid applied, polyurethane based, waterproofing membrane  | 25KG | 20-25M2@2COAT            |
| SikaLastic 640TC     | يتم استخدامه فوق طبقة العزل لزيادة حمايته من العوامل الجوية | single component, polyurethane based, solvent containing topcoat for UV protection of polyurethane membranes   | 20KG | 100-130 M2               |
| SIKA LASTIC 862      | عزل مائي للأسطح والأساسات                                   | A two-component, elastic waterproofing membrane applied by roller or spray, suitable for concrete protection in exposed and buried structures.           |      | ~2-3 KG/M <sup>2</sup>   |
| SIKALASTIC 505       | عزل أسطح مرن  | Elastic waterproofing membrane with high crack-bridging ability, used for roofs and wet area   | 25KG | ~1.5-2 KG/M <sup>2</sup> |
| SIKALASTIC 383       | عزل مائي وحماية للخرسانة                                    | Elastic waterproofing membrane with high crack-bridging ability, used for roofs and wet areas.   | 25KG | ~1.5-2 KG/M <sup>2</sup> |
| SIKALASTIC 560       | عزل أسطح مقاوم للأشعة                                       | UV-resistant liquid membrane for roofs, provides durable waterproofing with high elasticity.   | 20KG | ~1.5-2 KG/M <sup>2</sup> |
| عزل مياه داخلي       |   |  |      |                          |
| Product              |   | Description  | Size | Coverage                 |
| Sika TOP 550M        | عزل الجدران الداخلية  | a two-component acrylic modified cementitious coating that requires on site mixing to form product to waterproof and resurface concrete                  | 20KG | 2KG/M2@1MM               |
| Sika TOP 550F        | عزل الابار  | a two-component acrylic modified cementitious coating that requires on site mixing to form product to waterproof and resurface concrete                  | 20KG | 2KG/M2@1MM               |
| Sika TOP 550J        | عزل الابار  | a two-component acrylic modified cementitious coating that requires on site mixing to form product to waterproof and resurface concrete                  | 20KG | 2KG/M2@1MM               |
| Sika Lastic HLM 5000 | تحت البلاط او عزل الجدران الاستنادية                        | a one-component, moisturecuring, bitumen-modified polyurethane elastomeric waterproofing membrane for exterior below-grade or between slab applications. | 25KG | 20-25M2@2COAT            |

| عزل مياه داخلي ملامسة ل مياه الشرب وبرك السباحة |                      |   |        |            |
|---|----------------------|---|--------|------------|
| Product   | سبب الإستخدام        | Description   | Size   | Coverage   |
| Sika TOP 550M                                   | عزل الجدران الداخلية | a two-component acrylic modified cementitious coating that requires on site mixing to form product to waterproof and resurface concrete | 20KG   | 2KG/M2@1MM |
| Sika TOP 550F                                   | عزل الالبار          | a two-component acrylic modified cementitious coating that requires on site mixing to form product to waterproof and resurface concrete | 20KG   | 2KG/M2@1MM |
| Sika TOP 550J                                   | عزل الالبار          | a two-component acrylic modified cementitious coating that requires on site mixing to form product to waterproof and resurface concrete | 20KG   | 2KG/M2@1MM |
| SikaGard 180                                    | عزل وحماية الخرسانة  | Two-Part Epoxy-Based Protective Coating   | 6.2 KG | 9-12 M2    |
| SikaGard 190                                    | عزل وحماية الخرسانة  | A two component solvent free high build flexible epoxy polyurethane resin coating system  | 6.2 KG | 9-12 M2    |

| ارضيات اليبوكسي |   |  |  |          |
|-----------------|---|--|--|----------|
| Product         |   | Description  | Size   | Coverage |
| SikaFloor 1205  | تغطية الاررضية  | pigmented, high build epoxy floor and wall coating system designed to offer seamless durable floor protection at applied thicknesses between 0.2 to 0.50mm | Supply &Apply (Deppending on the status & the area of the floor) |          |
| SikaFloor 1230  | ايبوكسي بص سماكة اعلى وقوة تحمل للمركبات                | Self smoothing solvent free, epoxy overlay system for concrete floors @ 2 mm   |  |          |
| SikaFloor 1200  | طبقة اساس لارضيت اليبوكسي                               | LOW VISCOSITY, EPOXY RESIN PRIMER AND SEALER FOR CONCRETE FLOORS   |  |          |
| SIKADUR-31      | معدونة لتصلح الفتحات والتشققات في الارضيات قبل اليبوكسي | High strength, non-flow, epoxy bedding and repair mortar   |  |          |
| Sikafloor 430   | لتصليب سطح الباطون                                      | Premixed dry shake surface floor hardener  | 25KG   | 9-12/M2  |

| العزل الحراري        |                      |  |        |                             |
|----------------------|----------------------|--|--------|-----------------------------|
| Product              |                      | Description  | Size   | Coverage                    |
| ECOPEARL SHPU-35-34A | عزل حراري            | Spray applied polyurethane foam for seamless, high performance thermal insulations @ 35 kg/m3                              | M2     | Deppending on the thickness |
| ECOPEARL SHPU-35-34A | عزل حراري            | Spray applied polyurethane foam for seamless, high performance thermal insulations @ 35 kg/m3                              | M2     | Deppending on the thickness |
| عزل الحجر            |                      |  |        |                             |
| Product              |                      | Description  | Size   | Coverage                    |
| SIKAGARD SILICONE    | عزل للواجهات الحجرية | Colourless Silicone Based Surface Applied Water-Resisting Compound   | 22.5L  | 80-100M2                    |
| SIKAGARD HI 15       | عزل للواجهات الحجرية | Clear hydrophobic impregnation for concrete and masonry surfaces, reduces water absorption and protects against weathering | 20 LTR | 80-100M2                    |

| إصلاحات الخرسانة |                        |  |      |          |
|------------------|------------------------|--|------|----------|
| Product          |                        | Description  | Size | Coverage |
| Sika Grout 980   | تصليح خرسان انسيابي    | High strength, shrinkage compensated, cementitious deep pour precision grout for thickness >100 mm             | 25KG | -        |
| Sika Grout 928   | تصليح خرسان انسيابي    | Non-shrink grout with high early strength for base plates and heavy equipment                                  | 25KG | -        |
| SIKA GROUT 544   | تسكير قناحت ال tie rod | High strength, non-shrink, cementitious mortar   | 25KG | -        |
| SIKA GROUT 486   | تصليح التعشيش العميق   | grout for filling voids and structural strengthening   | 25KG | -        |
| SIKA EMACCO 303  | تصليح وجه الخرسانة     | Single component polymer modified fairing coat / cosmetic mortar for concrete surfaces                         | 25KG | -        |
| SIKA EMACO N900  | تصليح وجه الخرسانة     | , is cement based one component, polymer and fibre modified repair mortar for finishing the concrete surfaces. | 25KG | -        |

| معالجة فواصل التمدد |                              |  |                 |          |
|---------------------|------------------------------|--|-----------------|----------|
| Product             |                              | Description  | Size            | Coverage |
| SikaFlex 428        | تعينة الفواصل                | Flexible sealant for concrete precast  | 600 ML          | -        |
| BACKING ROD         | تعينة الفواصل قبل ال sealant | Closed-cell foam rod used as backing material for sealants   | Different SIZES | -        |
| SikaPolysulphide GG | تعينة الفواصل قبل ال sealant | is a cross linking polysulphide based elastic sealant for vertical and horizontal expansion joints |                 |          |
| SikaPolysulphide PG | تعينة الفواصل قبل ال sealant | s a cross linking polysulphide based elastic sealant for horizontal expansion joints               |                 |          |
| AR100 Z/10 CM       | تغطية الفواصل                | ALUM COVER   |                 |          |

| حماية طبقة العزل |                  |   |        |          |
|------------------|------------------|---|--------|----------|
| Product          |                  | Description   | Size   | Coverage |
| Dimple Sheet     | تغطية طبقة العزل | HDPE drainage sheet used for protection and drainage of waterproofing membranes | 600 ML | -        |

| توزيع الحديد وإضافة الباطون الجديد فوق القديم |                               |  |        |          |
|---|-------------------------------|--|--------|----------|
| Product                                       |                               | Description  | Size   | Coverage |
| SikaAnchor Fix -1Q                            | توزيع قضبان وبراغي الحديد     | adhesive anchoring system has been specially formulated as a high-performance, two component adhesive anchor system for threaded and reinforcing bars in uncracked concrete. | 300 ML | -        |
| SikaDur 1414                                  | التصاق الباطون القديم بالجديد | Wet-to-dry and vertical dowel Epoxy bonding agent for concrete repairs, bonding concrete to concrete, steel and granolithic toppings   | 3KG    | -        |

| عزل خزانات المياه العادمة |                            |  |      |          |
|---------------------------|----------------------------|--|------|----------|
| Product                   |                            | Description  | Size | Coverage |
| SikaGard 1812             | عزل لخزانات المساه العادمة | s a two component, solvent free, highly chemical resistant, pitch free epoxy coating | 25KG | -        |

| تنفيذ ومعالجة فواصل الصب      |           |  |        |          |
|-------------------------------|-----------|--|--------|----------|
| Product                       |           | Description  | Size   | Coverage |
| SikaWaterBar 940 @ 20 & 25 CM | ووتر ستوب | PVC waterstop for sealing construction   | 20 MTR | -        |
| SikaSwell A                   | وتر بار   | hydrophilic swelling sealant that expands upon contact with water to seal joints | 10 MTR |          |